

WF-7 is a Professional fingerprint access control & time and attendance terminal using the fingerprint instead of card system for access. The product experiences the strict degradation test before leaving factory, and all the input /output communication using anti-jamming protection. With this benefits, WF-7 provide a secure life for you that you could be no longer worrying about any irresponsible people entering your room.

WF-7 can be widely used in confidential places fo its easy installation and high security.

WF-7 is the best choice for you today to secure your life tomorrow!



Features and benefits:

High Security And Easy Installation

WF-7provide automatic alarm trigger in case of break in , door ajar and illegal dismantle of reader for safety precaution

Versatile Interface Options

RS232, RS485,TCP/IP, and Wiegand 26-bits (output)communication interface

Easy Enrollment And Fast Verification: A single fingerprint template enrollment takes about 3 seconds and verification takes less than 2 seconds per user

Waldso Inc. reserved the copyright of this page, if any change occured, Waldso is not responsible to notice in advance.

Model WF-7

Specification

Operation

Sensor: Waldso Optical Sensor (Scratch-proof)

Firmware Manufacturer: Waldso Inc.

Firmware Version: WaldsoFinger Version 2009
Algorithm version: WaldsoFinger VX9.0

Hardware platform: WEM500

Operating system: Linux

Operating Temperature: 0° C-45 $^{\circ}$ C Operating Humidity: 20%-80%

Storage

User Capacity 500 /Max.3000 (optional)
Transaction Storage 30000 /Max.50000(optional)

Communication

Communications RS232, RS485, TCP/IP, Wiegand

output (26-bits)

Enrollment & Verification

1:1 or 1 : N Multi-verification | Identification time \leq 2S | FAR < =0.0001% | FRR < =0.01%

LED Red, Green

LCD 128*64 White background light

Access Control Function

50 time zone function, group function unlocking combination function webserver(optional),

Time & Attendence Function

Standard: English, Function Keys Optional: Multi-National Language

> Timing State Switch Printer,work code, SMS


printer, RIS


Power

12V DC

Dimensions

L 145mm \times W 90.mm \times D 35mm





© 2009 Waldso Inc. All rights reserved.

