

Biometric Tripod Turnstile



TS2200 Tripod Turnstile
TS2211 Tripod Turnstile with Controller and RFID Reader
TS2222 Tripod Turnstile with Controller and Fingerprint & RFID Reader

Tripod turnstiles are compact and cost-effective entrance solutions. Designing for smooth and silent operation, reducing power consumption, wear and tear. It is suitable for areas with a high traffic.

The TS2200 series offer a well-designed, two-legged casework made of stainless steel, ideal for sites where a high traffic and robustness are issued. The TS2200 series have two passage channels in one casework, it is cost-effective for the application.

By receiving a signal from the access control system, or pushing button, it allows the entry of one person in a time. The status is shown on the led-way mode indicators on the top. Entering into different directions are electronically controlled. Default mode is to lock the mechanism until a valid authorization signal is received. If you want to set one side free, you can adjust the mechanism. In case of emergency, the horizontal arm will drop to allow free passage. Led way mode indicators are included as standard.

Features



Reliability

- · Alloy steel tripod hub prevents mechanical wear
- · Casework and tripod arms manufactured in SUS304 stainless steel
- Electromagnets for lock are used only when being activated. They are in standby mode when the device is idle. • ZK patented compact mechanism ensures

 - High quality electrical components



Safety and humanization design

- Drop arm designed for emergency purpose
- No exposed screws, safer for the user.
- · Smooth operation designed for mas transit application
- The pictogram on the device indicating access permission and direction of movement
- Special designed case shape, user-friendly for passenger to punch card or finger.
- Anti-tailgate
- · Well-designed electronic protection cover. Neat wiring inside.

Easy Integration

- Flexible reader installation plate. Customers can easily integrate with third party redaer
- Standard electrical interface for third party device.
- Using compact mechanism, the turnstile has more space inside for integration
- ZKTeco provides integration service in factory, with board and peripherals installed, ensuring compliance of the system. When the turnstile is delivered, just plug it in and do the setting. Save the cost of installation.
- The design of being vacuum at the bottom part of the device, enables easy installation for other hardwares.







Specifications


Power Supply	AC 220V/110V, 50/60Hz		
Operating Temperature	-28 °C- 60 °C		
Operating Humidity	5%-85%		
Working Environment	Indoor/Outdoor(shelter)		
Rated Power	60W		
Flow Rate	25-48 passage/minute		
Casework Material	SUS304		
Pictogram Indication	Yes		
Control System	Input controlled by dry contact		
Emergency Button Input	Yes		
Dimension	111×98×32(CM) + arm length 50CM		
Package Dimension	120×108×44(CM)		
Net Weight	65KG		
Gross Weight with Package	75KG		
Optional Function	Alternative material or shape, third-party access control integration,		
	ticket system integration, passage counter		

Model	TS2200	TS2211	TS2222
Access Control	N/A	C3-400	InBio460
Reader	N/A	4*KR100E	4*FR1200
Card Capacity	N/A	30,000	30,000
Fingerprint Capacity	N/A	N/A	3,000
Event Capacity	N/A	100,000	100,000

Dimensions (mm)







ZKTeco Inc.









© Copyright 2015. ZKTeco Inc. ZKTeco Logo is a registered trademark of ZKTeco or a related company. All other product and company names mentioned are used for identification purposes only and may be the trademarks of their respective owners. All specifications are subject to change without notice. All rights reserved.